

Model	B3055 4WD	B3065 4WD	B3085 4WD	B3095 4WD	B3105 4WD
Engine	FPT	FPT	FPT	FPT	FPT
Emission Level	Stage V	Stage V	Stage V	Stage V	Stage V
Engine Type	F28TCA	F28TCA	F28TCA	F28TCA	F28TCA
Max. Engine Power [kW/hp/rpm] [ISO14396]	43/58/2300	50/68/2300	55/75/2300	67/91/2300	75/102/2300
Max. Engine Torque [Nm/rpm]	250/1400	323/1400	375/1400	382/1500	415/1500
Cylinder Volume [cm ³ /number of cylinders]	2797/4	2797/4	2797/4	2797/4	2797/4
Cylinder Diameter x Stroke [mm]	91x108	91x108	91x108	91x108	91x108
Air Filter System	Dry air filter with clogging indicator	Dry air filter with clogging indicator	Dry air filter with clogging indicator	Dry air filter with clogging indicator	Dry air filter with clogging indicator
Air Intake	Turbo&Intercooler	Turbo&Intercooler	Turbo&Intercooler	Turbo&Intercooler	Turbo&Intercooler
Fuel Tank [lt]	70	70	70	70	70
Ad Blue Tank [lt]	-	-	-	13	13
Transmission					
Number of Gears	12 Forward + 12 Reverse	12 Forward + 12 Reverse	12 Forward + 12 Reverse	12 Forward + 12 Reverse	12 Forward + 12 Reverse
Clutch	Dry Type Dual Disc	Dry Type Dual Disc	Dry Type Dual Disc	Dry Type Dual Disc	Dry Type Dual Disc
Max. Speed [km/h-rpm]	37-2350	37-2350	37-2350	37-2350	37-2350
Diff. Lock & Front Axle					
Differential Lock	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic
4WD Traction	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic
PTO					
Type	Independent Dual Speed	Independent Dual Speed	Independent Dual Speed	Independent Dual Speed	Independent Dual Speed
Rear PTO Speed [rpm]	540-540E	540-540E	540-540E	540-540E	540-540E
Front PTO Speed [rpm]	-	-	-	1000	1000
Rear Axle and Brakes					
Rear Braking System	Multi Pads,wet type and hydraulic	Multi Pads,wet type and hydraulic	Multi Pads,wet type and hydraulic	Multi Pads,wet type and hydraulic	Multi Pads,wet type and hydraulic
Parking Brake	Mechanic	Mechanic	Mechanic	Mechanic	Mechanic
4WD Engagement System With Brake	Standard	Standard	Standard	Standard	Standard
Hydraulics and Rear 3-point Hitch					
Max. Hydraulic Flow / Pump Pressure [(lt/min)/bar]	45/190	45/190	45/190	45/190	45/190
Fuctions	Position, Draw, Sensitivity	Position, Draw, Sensitivity	Position, Draw, Sensitivity	Position, Draw, Sensitivity	Position, Draw, Sensitivity
Auto Lift	Standard	Standard	Standard	Standard	Standard
Hydraulic Remote [Out/valve]	4/2 - 6/3	4/2 - 6/3	4/2 - 6/3	8/4	8/4
Lift Control	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Max. Lifting Capacity [kg]	3000	3000	3000	3000	3000
Weights and Dimensions					
Shipping Weight [kg]	2800	2800	2800	2900	2900
Front Weight [number x kg]	6x22	6x22	6x22	6x22	6x22
Rear Weight [number x kg]	2x45/2x30	2x45/4x30	2x45/4x30	2x45/4x30	2x45/4x30
Total Length Without Front Weights [mm]	3920	3920	3920	3960	3960
Wheelbase [mm]	2180	2180	2180	2220	2220
Front Track Width [mm]	1140-1340	1140-1340	1140-1340	1140-1340	1140-1340
Rear Track Width [mm]	1210-1490	1210-1490	1210-1490	1210-1490	1210-1490
Total Width [mm]	1770	1770	1770	1770	1770
Total Height [mm]	2593	2593	2593	2593	2593
Tyres					
1. option [front]	280/70R16	280/70R16	280/70R16	280/70R16	280/70R16
1. option [rear]	380/70R24	380/70R24	380/70R24	380/70R24	380/70R24
2. option [front]	280/70R18	280/70R18	280/70R18	280/70R18	280/70R18
2. option [rear]	380/85R24	380/85R24	380/85R24	380/85R24	380/85R24
3. option [front]	280/70R18	280/70R18	280/70R18	280/70R18	280/70R18
3. option [rear]	340/85R28	340/85R28	340/85R28	340/85R28	340/85R28

Hattat Traktör Sanayi ve Ticaret A.Ş. bu broşürde belirtilen çizimlerin ve teknik bilgilerini değiştirme hakkını saklı tutar.