

Model	C3055 4WD Rear Roll-Bar	C3065 4WD Rear Roll-Bar	C3085 4WD Rear Roll-Bar	C3055 4WD Cabin	C3065 4WD Cabin	C3085 4WD Cabin
<b>Engine</b>	<b>FPT</b>	<b>FPT</b>	<b>FPT</b>	<b>FPT</b>	<b>FPT</b>	<b>FPT</b>
Emission Level	Stage V	Stage V	Stage V	Stage V	Stage V	Stage V
Engine Type	F28TCA	F28TCA	F28TCA	F28TCA	F28TCA	F28TCA
Max. Engine Power [kW/hp/rpm] [ISO14396]	43/58/2300	50/68/2300	55/75/2300	43/58/2300	50/68/2300	55/75/2300
Max. Engine Torque [Nm/rpm]	250/1400	323/1400	375/1400	250/1400	323/1400	375/1400
Cylinder Volume [cm <sup>3</sup> /number of cylinders]	2797/4	2797/4	2797/4	2797/4	2797/4	2797/4
Cylinder Diameter x Stroke [mm]	91x108	91x108	91x108	91x108	91x108	91x108
Air Filter System	Dry air filter with clogging indicator	Dry air filter with clogging indicator	Dry air filter with clogging indicator	Dry air filter with clogging indicator	Dry air filter with clogging indicator	Dry air filter with clogging indicator
Air Intake	Turbo&Intercooler	Turbo&Intercooler	Turbo&Intercooler	Turbo&Intercooler	Turbo&Intercooler	Turbo&Intercooler
Fuel Tank [lt]	80	80	80	80	80	80
<b>Transmission</b>						
Number of Gears	12 Forward + 12 Reverse	12 Forward + 12 Reverse	12 Forward + 12 Reverse	12 Forward + 12 Reverse	12 Forward + 12 Reverse	12 Forward + 12 Reverse
Clutch	Dry Type Dual Disc	Dry Type Dual Disc	Dry Type Dual Disc	Dry Type Dual Disc	Dry Type Dual Disc	Dry Type Dual Disc
Max. Speed [km/h-rpm]	37-2350	37-2350	37-2350	37-2350	37-2350	37-2350
<b>Diff. Lock &amp; Front Axle</b>						
Differential Lock	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic
4WD Traction	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic
<b>PTO</b>						
Type	Independent Dual Speed	Independent Dual Speed	Independent Dual Speed	Independent Dual Speed	Independent Dual Speed	Independent Dual Speed
Rear PTO Speed [rpm]	540-540E	540-540E	540-540E	540-540E	540-540E	540-540E
<b>Rear Axle and Brakes</b>						
Rear Braking System	Multi Pads,wet type and hydraulic	Multi Pads,wet type and hydraulic	Multi Pads,wet type and hydraulic	Multi Pads,wet type and hydraulic	Multi Pads,wet type and hydraulic	Multi Pads,wet type and hydraulic
Parking Brake	Mechanic	Mechanic	Mechanic	Mechanic	Mechanic	Mechanic
4WD Engagement System With Brake	Standard	Standard	Standard	Standard	Standard	Standard
<b>Hydraulics and Rear 3-point Hitch</b>						
Max. Hydraulic Flow / Pump Pressure [(lt/min)/bar]	45/190	45/190	45/190	45/190	45/190	45/190
Fuctions	Position, Draw, Sensitivity	Position, Draw, Sensitivity	Position, Draw, Sensitivity	Position, Draw, Sensitivity	Position, Draw, Sensitivity	Position, Draw, Sensitivity
Auto Lift	Standard	Standard	Standard	Standard	Standard	Standard
Hydraulic Remote [Out/valve]	6/3	6/3	6/3	6/3	6/3	6/3
Max. Lifting Capacity [kg]	3000	3000	3000	3000	3000	3000
Lift Control	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
<b>Weights and Dimensions</b>						
Shipping Weight [kg]	2900	2900	2900	3350	3350	3350
Front Weight [number x kg]	6x22/8x22	8x22	8x22	6x22/8x22	8x22	8x22
Rear Weight [number x kg]	2x45	2x45/4x45/2x70	2x45/4x45/2x70	2x45	2x45/4x45/2x70	2x45/4x45/2x70
Total Length Without Front Weights [mm]	3889	3889	3889	3934	3934	3934
Wheelbase [mm]	2180	2180	2180	2180	2180	2180
Front Track Width [mm]	1140-1560	1140-1560	1140-1560	1140-1340	1140-1340	1140-1340
Rear Track Width [mm]	1210-1440	1210-1440	1210-1440	1210-1490	1210-1490	1210-1490
Total Width [mm]	2040	2040	2040	1760	1760	1760
Total Height [mm]	2445	2445	2445	2632	2632	2632
<b>Tyres</b>						
1. option [front]	280/70R20	300/70R20	300/70R20	280/70R20	300/70R20	300/70R20
1. option [rear]	14.9/13-28	380/85R30	380/85R30	14.9/13-28	380/85R30	380/85R30
2. option [front]	280/70R18	280/85R20	280/85R20	280/70R18	280/85R20	280/85R20
2. option [rear]	340/85R28	12.4/11-36	12.4/11-36	340/85R28	12.4/11-36	12.4/11-36
3. option [front]	300/70R20	300/70R20	300/70R20	300/70R20	300/70R20	300/70R20
3. option [rear]	14.9/13-30	14.9/13-30	14.9/13-30	14.9/13-30	14.9/13-30	14.9/13-30
4. option [front]	300/70R20			300/70R20		
4. option [rear]	380/85R30			380/85R30		

Hattat Traktör Sanayi ve Ticaret A.Ş. bu broşürde belirtilen dizaynları ve teknik bilgilerini değiştirme hakkını saklı tutar.